

# HH



**HETRONIC**  
CENTRAL BALTIC

# TECHNICAL SALES SHEET

## ○ Transmitter Type: HH

- **Housing:**  
Ergonomically designed housing,
- **Housing Material:**  
Impact Resistant Polymer Composite
- **Environmental Protection:**  
IP 65
- **Weight:**  
510 g (1.1 lbs) includes batteries
- **Dimensions:**  
Height: 205 mm, 8.0 in  
Width: 132 mm, 5.2 in  
Depth: 86 mm, 3.4 in
- **Operation Time:**  
Up to 20 h continuous transmission
- **Power Supply:**  
2 AA batteries (3 Mignon LR6-AA 1.5 V)
- **Transmitter Options**  
Depending on configuration customers
- **Frequency Range:**  
419 MHz, 429 MHz, 434 MHz, 447 MHz,  
458 MHz, 868 MHz
- **RF Unit:**  
Type CS synthesized
- **Power (RF Output):**  
< 10 mW
- **Typical Operating Range:**  
Up to 100 m (300 ft)
- **Safety Address:**  
20-bit (over 999,999 possibilities)  
Address Module (ADMO)
- **Safety:**
  - 20-bit programmable address concept with up to 1 million combinations
  - Active and passive Stop function
  - Parity & Checksum
- **Temperature Range:**  
-25°C to 70° C (-13° F to 158° F)
- **Humidity Range:**  
0 - 97% non-condensing
- **Response Time:**  
Less than 100 msec.

